

M12 CONNECTIVITY ESSENTIALS

| DISTRIBUTION BOX

Murrelektronik distribution boxes offer solutions for a diverse array of applications. Space saving and maintenance friendly, they offer a 25% cost reduction compared to junction boxes and can be installed in a quarter of the time.



Art. Number: 8000-88410-3620500

Signals per Port: 2 Art. Number: 8000-88510-3980500



| EXACT12: 8-WAY with Field Wireable Cap Plug Signals per Port: 1

Art. Number: 8000-88450-0000000

Signals per Port: 2 **Art. Number:** 8000-88550-0000000



maintenance time.

| FIELD WIRED / T-SPLITTER

Murrelektronik T-Splitters and Field Wired connectors maximize

expenditures, simplifies installation and saves manpower and

capacity and efficient use of space. This lowers equipment

MALE M12, 4-pole, IDC

Operating Voltage: max. 32V AC/DC Connection Diameter: .25 - .5mm² Cable Diameter: 4-5.1mm Art. Number: 7000-12481-0000000



FEMALE M12, 4-pole, IDC

Operating Voltage: max. 32V AC/DC Connection Diameter: .25 - .5mm² Cable Diameter: 4-5.1mm Art. Number: 7000-12601-0000000



CONNECTORS

| FEMALE M12

Straight, 4-pole, Yellow PVC

Length: 2m **Art. Number:** 7000-12221-0140200

Length: 5m

Art. Number: 7000-12221-0140500

Length: 10m Art. Number: 7000-12221-0141000





Murrelektronik molded cable connectors provide the fastest means to

for installation. Additionally, our depth of variations solves application

| FEMALE M12

Length: 2m

Length: 5m

Length: 10m

Length: 1m

90°, 4-pole, Yellow PVC

Art. Number: 7000-12341-0140200

Art. Number: 7000-12341-0140500

Art. Number: 7000-12341-0141000

terminate a cable to a connector, while minimizing the tools needed

difficulties, providing cost savings through increased efficiency.

Art. Number: 7000-40021-0140300

Art. Number: 7000-40021-0140100

MALE to FEMALE M12

Straight, 4-pole, Yellow PVC

TORQUE WRENCH

Murrelektronik's unique torque wrench ensures connectors are tightened to precisely the right degree. Turn the wrench until it clicks and guarantee long-term, consistent connection quality with IP67 protection.


M12 TORQUE WRENCH

Art. Number: 7000-99102-0000000

| M8 TORQUE WRENCH

Art. Number: 7000-99101-0000000

The practical torque wrench connects all Murrelektronik M8 & M12 connectors simply and tightly, leaving no room for error.



1. Connector is not screwed tight. Medium can penetrate between connector and O-ring.

2. Connector is screwed too tight. O-ring is destroyed and medium can penetrate between connector and O-ring.

3. M12 connector is best tightened to 0.6 Nm. Then it's sealed tight!

M12/M8 CONNECTORS Save Time Reduce Errors



Signals per Port: 1

M12 PORT PLUG

Art. Number: M12-PLUG-PA



| EXACT12: 8-WAY Molded Cap and 5m Cable

Number of Poles: 1 Art. Number: 8000-88459-3620500

Number of Poles: 2 Art. Number: 8000-88559-3980500



| MALE M12, 4-pole, SCREW TERMINAL Operating Voltage: max. 250V AC/DC


Connection Diameter: max..75mm² Cable Diameter: 4-6mm

Art. Number: 7000-12701-0000000



| T-COUPLER, 5-pole, SLIM-LINE (For Splitting Signals)

Art. Number: 7000-41131-0000000









EXACT8: 8-WAY Molded Cap and 5m Cable

Signals per Port: 1 Art. Number: 8000-88010-3590500



MALE M8, 3-pole, IDC

| MALE M8, 4-pole, IDC

Operating Voltage: max. 32V AC/DC Connection Diameter: .25 - .5mm² Cable Diameter: 4-5.1mm Art. Number: 7000-08341-0000000



MALE M8, 3-pole, SCREW TERMINAL

Operating Voltage: max. 32V AC/DC Connection Diameter: .14 - .5mm² Cable Diameter: 3.5-5mm Art. Number: 7000-08601-0000000



| MALE M8, 3-pole, IDC

Operating Voltage: max. 32V AC/DC Connection Diameter: .14 - .34mm² Cable Diameter: 2.5-5.1mr Art. Number: 7000-08331-0000000



| FEMALE M8, 3-pole, IDC

Operating Voltage: max. 32V AC/DC Connection Diameter: .25 - .5mm² Cable Diameter: 4-5.1mm Art. Number: 7000-08361-0000000



| FEMALE M8

90°, 3-pole, Yellow PVC

Length: 5m

Art. Number: 7000-08081-0100500




Length: 3m **Art. Number:** 7000-08041-0100300

Length: 5m

Art. Number: 7000-08041-0100500

Length: 10m **Art. Number:** 7000-08041-0101000




• IP67 Rated

 LEDs for Signal Verification Pre-engineered Solutions

Fully Factory Tested

• IP67 Rated



Straight, 4-pole, Yellow PVC

Length: 5m Art. Number: 7000-08061-0110500

















M8 PORT PLUG Art. Number: 3858627